


MR1



MR2

WATERLINE



MR1

MISCELATORE DA INCASSO PER DOCCIA
 CONCEALED SHOWER MIXER
 MITIGEUR DE DOUCHE ENCASTRABLE
 MONOMANDO EMPOTRADO PARA DUCHA
 UP-BRAUSEMISCHER



MR2

MISCELATORE DA INCASSO PER DOCCIA, CON DEVIATORE AUTOMATICO A 2 VIE
 CONCEALED SHOWER MIXER, WITH 2-WAYS AUTOMATIC DIVERTER
 MITIGEUR DE DOUCHE ENCASTRABLE, AVEC INVERSEUR AUTOMATIQUE À 2 VOIES
 MONOMANDO EMPOTRADO PARA DUCHA, CON DESVIADOR AUTOMATICO 2 SALIDAS
 UP-BRAUSEMISCHER, MIT 2-WEGE AUTOMATISCHER UMSTELLER

DOTAZIONE

- Parti esterne in acciaio inox Aisi 316
- Cartuccia ceramica 35 mm

MR2: Deviatore automatico a 2 vie

EQUIPMENT

- Trim parts in inox steel Aisi 316
- Ceramic cartridge 35 mm

MR2: 2-ways automatic diverter

ÉQUIPEMENT

- Parties extérieures en inox Aisi 316
- Cartouche à disques ceramiques 35 mm

MR2: Inverseur automatique à 2 voies

EQUIPAMIENTO

- Componentes exteriores de acero inox Aisi 316
- Cartucho cerámico 35 mm

MR2: desviador automatico 2 salidas

AUSSTATTUNG

- Äußere Teile aus Edelstahl Inox Aisi 316
- Keramikkartusche 35 mm

MR2: 2-Wege automatischer Umsteller

Alimentazione:
 acqua calda e fredda
Dati Tecnici
 Pressione d'esercizio consigliata: 1 ÷ 5 Bar
 Collegamento alla rete: ½" F

Water supply:
 hot and cold water
Technical Info
 Recommended flow pressure: 1 ÷ 5 Bar
 Connection to water supply: ½" F

Alimentation:
 eau chaude et froide
Info Technique
 Pression de service conseillée: 1 ÷ 5 Bar
 Raccords à l'alimentation: ½" F

Alimentación:
 agua caliente y fría
Datos Técnicos
 Presión de trabajo aconsejada: 1 ÷ 5 Bar
 Enlace a la red: ½" H

Versorgung:
 warmes und kaltes Wasser
Technische Angaben
 Empfohlener Wasserdruck: 1 ÷ 5 Bar
 Anschluss mit Wasserversorgung-Rohr: ½" F